

SKID-STEER LOADER S530

Operating Weight 2815 kg 36.5 kW **Engine Power Rated Operating Capacity** 869 kg




S530 - SPECIFICATIONS

Performance

I GITUTITATICE	
Tipping load (ISO 14397-1)	1737 kg
Rated operating capacity (ISO 14397-1)	869 kg
Pump capacity	64.7 L/min
System relief at quick couplers	23.8-24.5 MPa
Max. travel speed (high range-option)	17.3 km/h
Max. travel speed (low range)	11.8 km/h
Engine	
Make/Model	Kubota/V2403 (iT4)
Fuel	Diesel
Cooling	Liquid
Power at 2700 RPM (SAE J1995 Gross)	36.5 kW (48.9 HP)
Forque at 1600 RPM (SAE J1995 Gross)	158.6 Nm
Number of cylinders	4
Displacement	2392 cm ³
Fuel tank	93.7 L
Weights	
Operating weight	2815 kg
Shipping weight without bucket	2476 kg
Controls	
Vehicle steering	Hand levers or optional Selectable Joystick Controls (SJC)
Loader hydraulics tilt and lift	Foot pedals or optional Selectable Joystick Controls (SJC)
Front auxiliary (standard)	Proportional switch on hand levers or optional Selectable
	Joystick Controls (SJC)
Drive System	
Transmission	Infinitely variable tandem hydrostatic piston pumps, driving
Standard Features	two fully reversing hydrostatic motors
Bobcat Interlock Control System (BICS)	Cushioned lift and tilt cylinders
Parking brake	Lift arm support
Operator cab ¹ dome light and electrical power port	Engine/hydraulics system shutdown
Operating lights, front and rear	Spark arrester
Standard seat	Automatically activated glow plugs
Seat belt	Electrically activated proportional front auxiliary hydraulics
Seat bar	Auxiliary hydraulics: variable flow/maximum flow
10x16.5, 10-ply, Heavy duty tyres	Manual
Bob-Tach™ frame	Back-up alarm
1. Roll Over Protective Structure (ROPS) – meets requirements of SAE-J10	040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements o
AE-J1043 and ISO 3449, Level I	
Options	
Deluxe pressurized cab with heating	2 speed
Selectable Joystick Controls (SJC-R/C Ready)	Power Bob-Tach™
Cloth suspension seat	Radio
10x16.5, 10-ply, Heavy duty tyres, offset rims	Beacon
10x16.5, 10-ply, Severe duty tyres	Road option
7-pin attachment control	Automatic ride control
Noise reduction kit	Automatic reversing fan
Deluxe instrument panel	Custom paint color (min order of 5 units)

Dimensions



(A)	3901.0 mm	(J)	3023.0 mm
(B)	1972.0 mm	(K)	828.0 mm
(C)	24.2°	(L)	42.0°
(D)	185.0 mm	(M)	97.0°
(E)	1082.0 mm	(N)	1727.0 mm
(F)	2657.0 mm	(0)	2024.0 mm
(G)	3378.0 mm	(P)	1374.0 mm
(H)	30.0°	(Q)	1643.0 mm
(I)	2319.0 mm		

achments

igle broom	Pallet fork
iger	Planer
ickhoe	Rock bucket
lle fork	Scarifier
ades — box, dozer, snow,	Scraper
ow v-blade	Seeder
eaker, hydraulic	Snow pusher
ush saw	Snowblower
ushcat™ rotary cutter	Sod layer
icket adapter	Soil conditioner
ickets	Spreader
lipper	Stabilizer, rear
mbination bucket	Steel tracks
oncrete mixer	Sweeper
gger	Three-point hitch adapter
op hammer	Tiller
Imping hopper	Tilt-Tatch™
ail cutter	Tree spade
ader	Trench compactor
apples — farm / utility,	Trencher
dustrial, root	Utility fork
ndplane	Utility frame
ndscape rake	Vibratory roller
ser equipment	Water kit
ower	Whisker broom
cker wheel	



Keyless start with password capability

Hydraulic bucket positioning (including ON/OFF switch)

Bobcat is a Doosan company. Doosan is a global leader in construction equipment, power and water solutions, engines, and engineering prouldy serving customers and communities for more than a century. | Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries. ©2020 Bobcat Company. All rights reserved.

Suspension seat



Doosan Bobcat Korea Co., Ltd. www.bobcat.com